

Fatpumpe APAC W1776



1776

TECHNICAL DATA	1773	1776	1775	1772	1776S
Compression ratio	1,4:1	3:1	3:1	3:1	3:1
Operating pressure min/max	5-10 bar	5-8 bar	5-8 bar	5-8 bar	5-8 bar
Delivery capacity	48 l/min	12 l/min	12 l/min	12 l/min	12 l/min
Air inlet connection	F 1/4"	F 1/4"	F 1/4"	F 1/4"	F 1/4"
Oil outlet connection	M 3/4"	M 1/2"	M 1/2"	M 1/2"	M 1/2"
Shaft lenght	950 mm	940 mm	730 mm	270 mm	1130 mm
Shaft diameter	55 mm	42 mm	42 mm	42 mm	42 mm
Max viscosity	SAE 120	SAE 150	SAE 150	SAE 150	SAE 150
Suitable for drums	180/220 l	180/220 l	50/60 l	murale wall mounted	1000 l
Air consumption	100 l/min	100 l/min	110 l/min	110 l/min	100 l/min
Noise level	82 db	82 db	82 db	82 db	82 db
Weight	6,5 kg	5,9 kg	5,7 kg	4,6 kg	5,9 kg

The manufacturing Company reserves the right to make modifications to its machines at any time without notice.