

JAX DRY-GLIDE® 3H SILICONE RELEASE

NSF H1 AND NSF 3H 100% SILICONE AEROSOL SPRAY



FOOD GRADE

PRODUCT DESCRIPTION

JAX Dry-Glide® 3H Silicone Release is clear, water-white dimethylpolysiloxane fluid used for food grade applications. It is NSF H1 and 3H compliant so it can be used both as an incidental contact lubricant and as a release agent. This 100% silicone fluid is manufactured under rigidly controlled conditions to ensure the highest quality and purity of product.

PRODUCT BENEFITS

- **Effective Release Agent**
- **Reduces Abrasion and Sticking**
- **Allergen Free**
- **Good Heat Stability**
- **Low Environmental Hazard**
- **Low Toxicity**
- **High Dielectric Strength**
- **High Oxidation Resistance**
- **High Compatibility**
- **High Water Repellency**
- **Non Grease**
- **Low Odor**
- **Low Reactivity**
- **Non-Bioaccumulating and Non-Bioactive**
- **Non Occlusive**
- **Tasteless**
- **Non Rancidifying**
- **Kosher and Parve Certified**
- **NSF H1 and 3H Registered**
- *JAX Dry-Glide 3H Silicone is available in Aerosol Spray*

APPLICATIONS

- Mold release agent
- Elastomer and plastics lubricant
- Electrical insulating fluid
- Foam preventative or breaker
- Surface active agent
- Friction reducer

COMPATIBILITY

Not compatible with water



JAX DRY-GLIDE® 3H SILICONE RELEASE

AEROSOL PRODUCT		
TYPICAL PROPERTIES	Dry-Glide 3H Silicone Release	METHOD
Propellant	Propane and Butane	
Flash Point	620°F (326°C) Silicone Fluid, Typical -94°F (-70°C) Propellant, Typical	ASTM D 92
Pour Point	-85°F (-65°C) Silicone Fluid, Typical	ASTM D 92
Spray Pattern	Very Fine Mist	
Viscosity	266 cSt @40°C Silicone Fluid	ASTM D 445
Texture	Evaporating Mist	
Appearance	Clear	
Consistency	Light	
Specific Gravity	0.977 for Concentrate, Typical	ASTM D 1298
NSF Registration No. / Category Code	148898 / 3H	

JAX products undergo continual improvement in formulation and manufacture. The values indicated in this PDS are typical production values at the time of this writing. JAX reserves the right to alter and update product data and typical values at any time without notice. It is the responsibility of the installer and/or purchaser to determine if these specifications are adequate and proper for the intended application. MSDS information may be found at www.jax.com or by contacting JAX INC.

CONTAINER SIZE

DRY-GLIDE 3H SILICONE RELEASE

Aerosol (12/cs)

JAX308

**JAX INC.**

Menomonee Falls, WI • Sacramento, CA • Nashville, TN
800.782.8850 • 262.781.8850 • www.jax.com

