

Food-Grade Anti-Seize

PRODUCT DESCRIPTION:

JAX Food-Grade Anti-Seize is a premium quality, food-grade, non-drying thread conditioner and anti-seize compound formulated with a balanced blend of PTFE and other lubricating solids, homogenized into a high melt grease carrier. JAX Food-Grade Anti-Seize meets the requirements of USDA H1 food-grade lubricants, and is acceptable in food, beverage and pharmaceutical applications where incidental food contact is possible.

PRODUCT BENEFITS:

JAX Food-Grade Anti-Seize has been engineered to provide a superior leak-proof seal for the life of the connection while maintaining its anti-seize and anti-corrosion capabilities. This allows for easy disassembly without the concern for thread and fastener damage. The JAX unique formulation is very resistant to high-pressure, high-temperature washdown common to the food- and beverage-processing industries.

APPLICATION:

JAX Food-Grade Anti-Seize is a dependable, quality sealant for threaded connections on lines carrying a variety of liquids and gases, including water, natural gas, LPG, beer, wine, juice, carbon dioxide, soups, dressings, vegetable washes, etc. JAX Food Grade Anti-Seize provides reliable service on brass, black iron, galvanized steel, stainless steel, aluminum, copper, PVC and fiberglass-reinforced pipes, tubes and connections.

JAX Food-Grade Anti-Seize provides lubrication from 10°F to 482°F (-12°C to 250°C). NLGI Grade 1-1/2. Product features include:

- Meets USDA H1 requirements
- Non-drying
- Lubricates threads
- Forms leak-proof seals
- Resists water and steam
- Economical
- Non-melting
- Easy to apply
- Prevents corrosion

TECHNICAL DATA:

| | <u>JAX134</u> | <u>JAX234</u> |
|--------------|--|--|
| Propellant: | N/A | Propane Butane |
| Flash Point: | 480° F (248°C), ASTM D 92, typical | Extremely Flammable |
| Viscosity: | N/A | N/A |
| Texture: | Creamy White Grease with PTFE and Other Particulates | Creamy White Grease with PTFE and Other Particulates |
| Appearance: | Thick White Grease-like | Tan Grease |
| Consistency: | Heavy | Heavy |

PACKAGING:

- 8-oz. net weight bottles with brush-top caps (12/case) – Part # JAX134
- 16-oz. net weight bottles with brush-top caps (12/case) – Part # 00134-121
- Pail – Part # 00134-035; Keg - Part # 00134-120
- 11-oz. net wt. aerosol cans (12/case) – Part # JAX234



Nonfood Compounds
Program Listed H1
Reg. # 127729



Food-Grade Anti-Seize



NSF International / Nonfood Compounds Registration Program

Nonfood Compounds
Program Listed

April 10, 2014

Ms. Patty Riek
Pressure-Lube, Inc. Jax
W134 N5373 Campbell Drive
Menomonee Falls, WI 53051
United States

RE: JAX FOOD-GRADE ANTI-SEIZE (AEROSOL)

Category Code: H1
NSF Registration No. 147053

Dear Ms. Patty Riek:

NSF has processed the application for Registration of JAX FOOD-GRADE ANTI-SEIZE (AEROSOL) to the NSF International Registration Guidelines for Proprietary Substances and Nonfood Compounds (2009), which are available at www.nsfwhitebook.org. The NSF Nonfood Compounds Registration Program is a continuation of the USDA product approval and listing program, which is based on meeting regulatory requirements including FDA 21 CFR for appropriate use, ingredient and labeling review.

This product is acceptable as a lubricant with incidental food contact (H1) for use in and around food processing areas. Such compounds may be used on food processing equipment as a protective anti-rust film, as a release agent on gaskets or seals of tank closures, and as a lubricant for machine parts and equipment in locations in which there is a potential exposure of the lubricated part to food. The amount used should be the minimum required to accomplish the desired technical effect on the equipment. If used as an anti-rust film, the compound must be removed from the equipment surface by washing or wiping, as required to leave the surface effectively free of any substance which could be transferred to food being processed.

NSF Registration of this product is current when the NSF Registration Number, Category Code, and Registration Mark appear on the NSF-approved product label, and the Registered product name is included in the current NSF White Book Listing of Nonfood Compounds at the NSF website (www.nsfwhitebook.org).

NSF Listing of all Registered Nonfood compounds by NSF International is not an endorsement of those compounds, or of any performance or efficacy claims made by the manufacturer.

Registration status may be verified at any time via the NSF website, at www.nsfwhitebook.org. Changes in formulation or label, without the prior written consent of NSF, will void Registration, and will supersede the on-line listing.

Sincerely,

Amanda Phelka
NSF Nonfood Compounds Registration Program

Company No: N05625

Distributed By:

PRESSURE-LUBE
America's Finest Lubricants

W134 N5373 Campbell Drive • Menomonee Falls, WI 53051
262.781.8850 • 800.782.8850 • FAX 262.781.3906
www.jax.com