



PRODUCT DESCRIPTION:

JAX Belt Dressing is an outstanding belt dressing product for use on leather, canvas and rubber drive belts that is now NSF H1-registered as a food-grade incidental contact lubricant. It contains no resins or asphalts, and will not collect dust, dirt or other airborne abrasive materials that can shorten the life of a drive belt. The exclusive formulation will keep drive belts clean and supple, with no residual build-up or accumulation.

PRODUCT BENEFITS:

JAX Belt Dressing lengthens the life of drive belts by preventing premature cracking and brittleness. When used on slipping belts, JAX Belt Dressing will help restore optimum power output while providing improved traction and allowing reduced belt tension.

APPLICATION:

JAX Belt Dressing is formulated to work equally well on:

- Flat or round rubber or composition V-belts
- Industrial belt drives
- Truck and automotive fan belts
- Farm machinery leather or canvas take-off belts
- High-load industrial compressor or generator belts

TECHNICAL DATA:

Propellant: Propane and n-Butane

Flash Point: -6°F (-21°C) Bulk Product, Tag, typical

Spray Pattern: Stream

Texture: Light Sticky Film
Appearance: Clear Straw Liquid

Consistency: Light

Specific Gravity: 0.70 for Concentrate, typical

AEROSOL PACKAGING:

10.5 oz. net weight aerosol cans (12/case) — Part # JAX107









Belt Dressing











NSF International / Nonfood Compounds Registration Program

July 7, 2010

Ms. Patty Riek Pressure-Lube, Inc. Jax W134 N5373 Campbell Drive Menomonee Falls, WI 53051 United States

RE: JAX BELT DRESSING (Aerosol) Category Code: H1 NSF Registration No. 143436

Dear Ms. Patty Riek:

NSF has processed the application for Registration of JAX BELT DRESSING (Aerosol) to the NSF International Registration Guidelines for Proprietary Substances and Nonfood Compounds (2009), which are available at www.nsfwhitebook.org. The NSF Nonfood Compounds Registration Program is a continuation of the USDA product approval and listing program, which is based on meeting regulatory requirements including FDA 21 CFR for appropriate use, ingredient and labeling review.

This product is acceptable as a lubricant with incidental food contact (H1) for use in and around food processing areas. Such compounds may be used on food processing equipment as a protective anti-rust film, as a release agent on gaskets or seals of tank closures, and as a lubricant for machine parts and equipment in locations in which there is a potential exposure of the lubricated part to food. The amount used should be the minimum required to accomplish the desired technical effect on the equipment. If used as an anti-rust film, the compound must be removed from the equipment surface by washing or wiping, as required to leave the surface effectively free of any substance which could be transferred to food being processed.

NSF Registration of this product is current when the NSF Registration Number, Category Code, and Registration Mark appear on the NSF-approved product label, and the Registered product name is included in the current NSF White Book Listing of Nonfood Compounds at the NSF website (www.nsfwhitebook.org). The NSF Registration Mark can be downloaded by clicking the "Download Registration Mark" link on the NSF website (www.nsfwhitebook.org).

NSF Listing of all Registered Nonfood compounds by NSF International is not an endorsement of those compounds, or of any performance or efficacy claims made by the manufacturer.

Registration status may be verified at any time via the NSF website, at www.nsfwhitebook.org. Changes in formulation or label, without the prior written consent of NSF, will void Registration, and will supersede the on-line listing.

Sincerely

Clifton Mclellan

NSF Nonfood Compounds Registration Program

Company No: N05625

Distributed By:

