

Mobil Brake Fluid DOT 4

Extra High Performance Hydraulic Brake Fluid

Product Description

Mobil Brake Fluid DOT 4 is an extra high performance hydraulic brake fluid for use in automotive disc, drum and anti-skid brake systems and clutch systems. Typical properties vary depending on the supplier of the fluid. Typical properties for brake fluids include: Density at 20° C, boiling point, wet boiling point, flash point, and viscosity at "40° and "100° C. Use Brand approval data with the local filling.

Features and Benefits

Mobil Brake Fluid DOT 4 is based on polyethylene glycol ether technology to provide the highest level of brake and clutch performance in modern as well as older model automotive and commercial vehicles. Key features and benefits include:

Features	Advantages and Potential Benefits
High boiling point	Consistent and safe brake performance under severe braking pressure
Minimum rubber component swell	Reduces leakage and loss of fluid to a minimum
Excellent corrosion protection	Extended life and reliability of brake system components

Applications

Mobil Brake Fluid DOT 4 is suitable for all disc, drum and anti-skid braking systems used in average to high performance vehicles requiring DOT 3 or DOT 4 level performance. Recommendations for use include:

- Use only in its concentrated form out of a previously unopened or well sealed container
- Always seal the container immediately after use as the fluid absorbs moisture from the atmosphere quite rapidly; this will reduce service life significantly.
- Never reuse drained brake fluid.
- Brake fluid can affect the vehicle paintwork, so remove spills immediately without rubbing.
- Brake fluid should be drained from the vehicle every two years or 40,000 Km (24,000 Miles) and refilled.
- Check Owners Operators Manual for details.

Specifications and Approvals

Mobil Brake Fluid DOT 4 meets or exceeds the following industry specifications:

FMVSS 116 DOT 4

FMVSS 116 DOT 3

SAE J1703

ISO 4925





Health and Safety

Based on available information, avoid contact with the skin and eyes. Do not siphon with the mouth. Keep the Brake Fluid container tightly closed. If poisoning occurs, contact a doctor or Poisons Information Centre. If swallowed, and if more than 15 minutes from a hospital, induce vomiting, preferably using Ipecac Syrup APF. If skin contact occurs, remove contaminated clothing and wash skin thoroughly. If in eyes, hold eyes open, flood with water for at least fifteen minutes and see a doctor. The Brake fluid container should not be used for any other purpose. This product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDSs are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

The Mobil logotype, the Pegasus design, and Brake Fluid DOT 4 are trademarks of Exxon Mobil Corporation, or one of its subsidiaries.