

Precision Regulator/ Digital Gauge Fluid Reservoirs



1-Liter Tank
7013460: 0-10 psi (0-0.7 bar)
7013489: 0-100 psi (0-7.0 bar)

5-Liter Tank
7013430: 0-10 psi (0-0.7 bar)
7013490: 0-100 psi (0-7.0 bar)

1-Liter Specifications

Models: 7013460: 0-10 psi (0-0.7 bar)
7013489: 0-100 psi (0-7.0 bar)
Tank body: cast aluminum cast aluminum
Capacity: 1 liter
Maximum Operating Pressure: 100 psi (7.0 bar)
Maximum Operating Temperature: 50°C (122°F)
Weight: 3.0 kg (6.60 lbs)
Height: 350 mm (13.75")
Diameter (Cover Maximum): 172 mm (6.75")

All necessary fittings and feed tubing are included with each reservoir.

5-Liter Specifications

Models: 7013430: 0-10 psi (0-0.7 bar)
7013490: 0-100 psi (0-7.0 bar)
Tank body: Cast aluminum cast aluminum
Capacity: 5 liter
Maximum Operating Pressure: 100 psi (7.0 bar)
Maximum Operating Temperature: 50°C (122°F)
Weight: 9.1 kg (20.1 lbs)
Height: 413 mm (16.25")
Diameter (Cover Maximum): 251 mm (9.85")

For Nordson EFD sales and service in over 30 countries, contact Nordson EFD or go to www.nordsonefd.com

East Providence, RI USA
USA & Canada: 800.556.3484;
+1.401.431.7000
info@nordsonefd.com

Dunstable, Bedfordshire, UK
0800 585733; +44 (0) 1582 666334
Ireland 00800 8272 9444
europe@nordsonefd.com

Nordson India Private Limited
+91 80 4021 3600
india@nordsonefd.com

China: +86 (21) 3866 9006
china@nordsonefd.com

Singapore: +65 6796 9522
sin-mal@nordsonefd.com

The Wave Design is a trademark of Nordson Corporation.
©2014 Nordson Corporation v080514

Precision tank air pressure control is essential to ensure consistent, accurate fluid deposits from the dispense valve.

EFD Precision Regulator/Digital Gauge tank reservoirs offer exceptional full-to-empty fluid pressure control.

Available in 0-10 psi (0-0.7 bar) for low viscosity fluids and 0-100 psi (0-7.0 bar) for medium to high viscosity fluids.

EFD Precision Regulator/Digital Gauge reservoir assemblies are the right choice for improved process control, performance and repeatability.

Features

- **Main air supply pressure variations:** Precision regulator holds output pressure consistently regardless of input pressure fluctuations.
- **Repeatability:** From one shift to the next, precision regulator/digital gauge can be reset to exact pressure setting – removing analog readout error.
- **Tighter setting tolerances:** Pressures can be set to tenths of psi.
- **Fast response, robust pressure regulator:** Better resolution in pressure control.

Benefits

- Precision fluid pressure regulation/digital readout for exacting fluid pressure control.
- Better process control.
- Provides critical control of important variable for EFD time/pressure valve system operation and performance.
- Reliable “full to empty” pressure control for 1 and 5 liter reservoirs.
- Meets performance standards necessary in Life Sciences industry.