

DETECTEUR GAZ

FUNCTIONALITY

Aqueous leak detector.

- For all inflammable and non-flammable compressed air and gas pipes, valves and connectors.
- For all rigid or flexible pressurised air or gas containers (metal bottles, inflatables, etc.).
- Suitable for all gases, even those at low pressure.
- Does not stain.
- No corrosive effect on metals.

Technical characteristics

Specifications	Characteristics
Appearance	Colourless liquid
Chemical type	Aqueous solution of surfactants
Propellant	Environmentally friendly and non-flammable
Density at +20 °C	1.01
Use on oxygen systems	< 2 bars

Use

Preparation

- Shake the can

Directions for use

- Minimum usage temperature: +5 °C
- Spray on the area to be checked.
- If there is a leak, bubbles will appear immediately

Material cleaning

- Detergent
- Avoid using solvents for cleaning

Storage

Store between +5 °C and +40 °C.

At +20 °C, the shelf life of the product in its original, sealed packaging is 3 years.

The Safety Data Sheet is available online at www.quickfds.com. The information provided in this data sheet is given in good faith and is the result of measurements done in our laboratory. Given the number of materials, the quality differences and the diversity of working methods, we recommend that users carry out preliminary testing under actual conditions of use.

This document may be modified without warning in line with changes to the products or according to our knowledge. We therefore recommend that you check that you have the latest version before using the product.