

## GEBEX LUB

### FUNCTIONALITY

#### Lubrication paste for plastic piping assembly

- § For indoor and outdoor use
- § Soluble in water
- § Suitable for all diameters
- § Excellent sliding properties
- § Prevents rubber seal ageing and deformation

### Technical Characteristics

Specifications	Characteristics
Appearance	Paste
Base	Aqueous
Colour	Translucent - white
pH	Basic (11 – 12)
Temperature of use	- 0°C to +60°C

### Application

#### Preparation

As required:

- § Clean the parts to be assembled, including the seal, without disassembling it.
- § Remove any traces of mud, earth or sand, etc.

#### Instructions for use

- § In accordance with the application instructions for the piping (every pipe range has specific seals which may require different operating procedures for lubrication), lubricate the end of the male socket and/or the end of the female socket and/or the seal
- § Bring the two parts together and assemble them, keeping them aligned (adjustment, niche, etc.) and clean, until they are in place

#### Material cleaning

- § Water

### Storage

Store at a temperature of between +5°C and +25°C away from frost.  
At 20°C, the product closed in its original packaging keeps for 3 years.

The information contained on the technical datasheet is provided in all good faith and results from measurements made in our laboratory. Given the number of materials, differences in quality and diversity of working methods, we recommend that users perform tests prior to application under actual conditions of use.

This document may be amended in keeping with product development and the state of our knowledge without prior notice and therefore it is recommended to check that you have the latest version before use.

The safety datasheet is available online at [www.quickfds.com](http://www.quickfds.com)