

# BDF Cling-Lube

## PRODUCT DESCRIPTION:

JAX BDF Cling-Lube was formulated and tested in conjunction with maintenance departments on the line in nationally recognized beef-processing plants requiring food-grade lubricants for overhead applications that would cling and not drip on the product. With its foaming formula and extreme "cling" characteristics, JAX BDF Cling-Lube met all requirements and exceeded expectations! Combined with extreme-pressure and antiwear additives, JAX BDF Cling-Lube is the superior lubricant to use in overhead food-grade applications.

## APPLICATION:

A partial list of JAX BDF Cling-Lube's applications includes:

- Overhead chains and conveyors
- Overhead trolleys and way guides
- Conveyors leading into or out of high-moisture or steam areas
- Locations that are hard-to-reach or where frequent lubricating is difficult or inconvenient

## TECHNICAL DATA:

Propellant:	Propane and Butane
Flash Point:	352° F (178° C) concentrate, typical -94° F (-70° C) propellant, typical
Spray Pattern:	Foam
Texture:	Thick Cling Film
Appearance:	Light Straw Color
Consistency:	Heavy

## AEROSOL PACKAGING:

11 oz. net weight aerosol cans (12/case) – Part # JAX214





NSF International / Nonfood Compounds Registration Program

October 03, 2002

Pressure-Lube, Inc. JAX  
Attn: Patty Riek  
W134 N5373 Campbell Drive  
Menomonee Falls, WI 53051

RE JAX BDF CLING-LUBE (AEROSOL)  
Category Code: H1  
NSF Registration No. 127730

Dear Patty Riek:

NSF has processed the application for Registration of **JAX BDF CLING-LUBE (AEROSOL)** to the *NSF Registration Guidelines for Proprietary Substances and Nonfood Compounds (2002)*, which are available at [www.nsf.org/usda](http://www.nsf.org/usda). The NSF Nonfood Compounds Registration Program is a continuation of the USDA product approval and listing program, which is based on meeting regulatory requirements including FDA 21 CFR for appropriate use, ingredient and labeling.

**This product is acceptable as a lubricant with incidental food contact (H1) for use in and around food processing areas. Such compounds may be used on food processing equipment as a protective anti-rust film, as a release agent on gaskets or seals of tank closures, and as a lubricant for machine parts and equipment in locations in which there is a potential exposure of the lubricated part to food. The amount used should be the minimum required to accomplish the desired technical effect on the equipment. If used as an anti-rust film, the compound must be removed from the equipment surface by washing or wiping, as required to leave the surface effectively free of any substance which could be transferred to food being processed.**

NSF Registration of this product is current when the NSF Registration Number, Category Code, and Registration Mark appear on the NSF-approved product label, and the registered product name is included in the current NSF White Book Listing of Nonfood Compounds at the NSF website (<http://www.nsf.org/usda>). The NSF Registration Mark can be downloaded from the NSF website, at [http://www.nsf.org/mark/download\\_marks.html](http://www.nsf.org/mark/download_marks.html).

NSF Listing of all registered Nonfood compounds by NSF International is not an endorsement of those compounds, or of any performance or efficacy claims made by the manufacturer.

Registration status may be verified at any time via the NSF web site, at <http://www.nsf.org/usda>. Changes in formulation or label, without the prior written consent of NSF, will void registration, and will supersede the on-line listing.

Sincerely,

Carmen Grindatti  
NSF Nonfood Compounds Registration and listing program

*Distributed By:*

**PRESSURE-LUBE**  
America's Finest Lubricants