



OEST ECONOL B

OEST ECONOL B 9

Description

OEST Econol B 5 PP is a solvent-free non water miscible universal release agent on base of special mineral oil raffinates. It is applied on sucking and non-sucking moulds of wood steel and plastic and is especially suitable for the application of manufacturing prefabricated parts and on concrete at construction sites. OEST Econol B 9 is also perfectly suitable as mixer protection in prefabricated parts and ready-mixed concrete factories.

Advantages: Excellent separation effect, good wetting, light colour, mild in odour, solvent-free

Application

OEST Econol B 9 should be applied thinly and constantly with the suitable spraying equipment (with flat spray nozzles and 3 up to 4 bar pressure) on the clean and dry moulding.

OEST Econol B 5 PP may **not** be diluted or mixed with other oils, water or solvents.

Storage life: In closed packings at least 36 months

Chemical and physical properties

Viscosity at 20 °C / DIN 51562 / [mm ² /s]	26
Viscosity at 40 °C / DIN 51562 / [mm ² /s]	13
Density at 15 °C / DIN 51757 / [g/cm ³]	0,85
Pour point / DIN ISO 3016 / [°C]	< -9
Flash point / DIN EN ISO 2592 / [°C]	180
Product code	BTM 20
Water hazard class (WGK)	1

Alle Angaben dieser Produktinformation entsprechen nach bestem Wissen dem derzeitigen Erkenntnisstand. Änderungen bleiben vorbehalten. Bei der Vielfalt der Anwendungsmöglichkeiten und Einsatzbedingungen bei den Verwendern können unsere Anwendungshinweise nur allgemein gehalten sein. Sie sind nicht auf jeden Einzelfall übertragbar und unverbindlich. Für Haftungsregelungen sind ausschließlich unsere Allgemeinen Verkaufs- und Lieferungsbedingungen maßgeblich.

DQS CERTIFICATION:
DIN EN ISO 9001
Reg.-Nr. 35 486